



WOVEN FABRICS FOR WORK AND PROTECTIVE

Pražská 18b/1470, 102 00 Praha 15, Czech Republic
Tel.: +420/224 253 816, 804, 828
E-mail: kamil@marexim.cz, pracovni@marexim.cz

FABRIC INFORMATION

ARTICLE NO:	SILVER REFLECTIVE TAPE art. TC 32-60
Retro-reflective performance	EN20471:2013
Durability of EN standard	even after 50 cycles washing in 60°C

CHARACTERISTICS

Top layer	glass bead
Underlying fabric	65% PES/ 35% Cotton
Width	2,5 cm, 3 cm, 5 cm

COMPOSITION

Glass bead	30%
Resin	30%
Underlying fabric	30%
Other	10%

PHYSICAL PERFORMANCE TEST EXPOSURE

Abrasion	BSEN 530: 1991
Flexion	ISO 7854: 1984
Low temperature	ISO 4675: 1990 (-20°C)
Temperature difference	12 hours 50 +/- 5°C, 20 hours -30 +/- 2°C
Washing	ISO 6330: 1984, Method 2A, 60 +/- 5°C – 50 cycles
Dry cleaning	ISO 3175: 1979 – 25 cycles

INSTRUCTION FOR APPLICATION

Cutting	cutting out, hand cutting, tearing
Sewing	more than 2mm from the edge of the reflective fabric
	not more than 12 stitches per inch (2,54 cm)
Sewing thread	100% PES

WASH CARE:



ISO 9001 REGISTERED COMPANY